


60V-005

Shape and size



Model	A	B	C	D	E	Lead.
	max.	max.	max	$\pm 0.75\text{mm}$	Min	Φ
60V-005	5.0mm	8.5mm	3.0mm	5.1	4.6mm	0.50

Lead wire material: tin-plated metal wire, $\Phi 0.50\text{mm}$.

Encapsulation material: Flame-retardant epoxy powder, meeting UL94V-0 requirements

Electrical performance

Maximum overload current	40A_{DC}	Maximum voltage	60V_{DC}
Maximum non-operating current $25^\circ\text{C} \pm 2^\circ\text{C}$	50mA	Minimum operating current 25°C	150mA
Starting zero-power resistor	$7.3\text{--}20\ \Omega$	Maximum resistance one hour after action	$40\ \Omega$

Testing conditions and delivery standards

Inspection items	Test	Delivery standard
Starting zero-power resistor	$25^\circ\text{C} \pm 2^\circ\text{C}$, Place in the air	$7.3\text{--}20\ \Omega$
Non-operating current	$25^\circ\text{C} \pm 2^\circ\text{C}$, 50mA , Maintain 60min	Non-operating
Typical action time	$25^\circ\text{C} \pm 2^\circ\text{C}$, 250mA , 12V	Less than 8S
Motion durability	60V , 40A , 24hr	No open flame or burning

Working temperature : -40°C to 85°C

Packaging conditions: 1000pcs per bag