


60V-020

Shape and size



Model	A	B	C	D	E	Lead.
	max.	max.	max	$\pm 0.75\text{mm}$	Min	Φ
60V-020	7.4mm	12.7mm	3.0mm	5.1	4.6mm	0.50

Lead wire material: tin-plated metal wire, $\Phi 0.50\text{mm}$.

Encapsulation material: Flame-retardant epoxy powder, meeting UL94V-0 requirements

Electrical performance

Maximum overload current	40A_{DC}	Maximum voltage	60V_{DC}
Maximum non-operating current $25^{\circ}\text{C} \pm 2^{\circ}\text{C}$	200mA	Minimum operating current 25°C	400mA
Starting zero-power resistor	$1.50\text{--}2.84\ \Omega$	Maximum resistance one hour after action	$4.49\ \Omega$

Testing conditions and delivery standards

Inspection items	Test	Delivery standard
Starting zero-power resistor	$25^{\circ}\text{C} \pm 2^{\circ}\text{C}$, Place in the air	$1.50\text{--}2.84\ \Omega$
Non-operating current	$25^{\circ}\text{C} \pm 2^{\circ}\text{C}$, 200mA , Maintain 60min	Non-operating
Typical action time	$25^{\circ}\text{C} \pm 2^{\circ}\text{C}$, 1000mA , 12V	Less than 5S
Motion durability	60V, 40A, 24hr	No open flame or burning

Working temperature : -40°C to 85°C

Packaging conditions: 1000pcs per bag